

New Coming Items

CONTRA ANGLES HEAD >>

- RT-HSGM
- Replacement Head For NSK SGM




MANOMETER >>

- RT-TB2
- Manometer For 2 Holes Handpiece






HIGH SPEED ROTORS >>

Photo	Model	Suitable For	Photo	Model	Suitable For
	RT-R45T	NSK PHATELUS 45/CH-QD SABAR OMS 45-II		RT-RADZ	SinoIADZ

ORING & WASHER >>

Photo	Model	Suitable For	Photo	Model	Suitable For
	RT-OR11	Contra Angle 0.8 X 0.4mm		RT-W29	Air Motor



BEARINGS >>

Photo	Model Size(mm)	Suitable For	Photo	Model Size(mm)	Suitable For	Photo	Model Size(mm)	Suitable For
	RT-B001CTN 3.175 x 6.35 x 2.38	NSK Type Bearing Without Cover		RT-B015 3 x 7.6/7.0 x 2.5	Russian Handpiece S 628-3		RT-B001SL 3.175 x 6.35 x 2.38	Stainless Steel Ball

HIGH SPEED IMPELLER >>


Photo	Model	Suitable For	Photo	Model	Suitable For	Photo	Model	Suitable For
	RT-IMWS	Midwest Stylus		RT-IMWX	Midwest GXT		RT-IMWTY	Midwest Tradition Lever

HANDPIECE CAPS >>

Photo	Model	Suitable For	Photo	Model	Suitable For
	RT-C20B	For Bien Air Implant 20:1		RT-CX450	NSK Ti-Max X450

LOW SPEED ROTORS AND GEARS >>

Photo	Model	Suitable For	Photo	Model	Suitable For	Photo	Model	Suitable For	Photo	Model	Suitable For
	RT-GR25LH	Kavo 25LH		RT-R20B	Bien Air Implant 20:1		RT-SSB200	Kavo Contra Angle		RT-SSB238	For NSK Straight Handpiece
	RT-HG25LH	Kavo 25LH		RT-HG25LP	Kavo 25LP		RT-HG95M	Kavo 25LP			
	RT-KVSH01	Kavo Straight Handpiece		RT-KVSH02	Kavo Straight Handpiece		RT-KVSH03	Kavo Straight Handpiece			

Photo	Model	Suitable For	Photo	Model	Suitable For
	RT-MG20B	Bien Air Implant 20:1			

REPAIRING TOOLS >>



- RT-TSH4
- C-Clip Wrench For NSK Straight Handpiece

- RT-T203C
- For NSK Air Motor

- RT-T25LP
- Cap Wrench For Kavo 25LP

- RT-T339
- Bearing Pressing Tool

TUBES >>



- RT-TUS
- Hoses For Dental Suction

- RT-TUP5
- Cable For Satelec NEWTRON P5 DTE With LED

- RT-010-F2
- Foot Pedal Double Row Tube

- RT-SNENDO
- Spray Nose For NSK Endo Mate



Dental Suction Hose Hoses - with plastic reinforcement

Structure: double walled, light and highly flexible PVC hose, with a double PP helix and yarn reinforcement along the axis

Applications: Special hose for dental devices and medical appliances, cable protection

Temperature range: 0°C to +40°C (short term up to +60°C)

I.D.Ø= d		O.D. = D		r (min.)	= Load capacity Vacuum	Length	Order No.
mm	Tolerance	mm	Tolerance	mm	millibars	m	
6	+/- 0,25	10	+/- 0,5	10	250	1.8m or 6m	DSH06
8		12		15	250		DSH08
9		13		16	250		DSH09
10		14		18	200		DSH10
11		15		19	200		DSH11
12		16		20	200	DSH12	
14		18		24	200	DSH14	
15		19		25	200	DSH15	
16		20		27	200	DSH16	
17		21		30	200	DSH17	
19		23		32	200	DSH19	
20		24		33	200	DSH20	
21		25		34	200	DSH21	
22		27		35	200	DSH22	
25		30		40	200	DSH25	

Other diameters on request